



**AKURATE**  
DYNAMICS

# Delta CPS-HV

## DOUBLE PROPORTIONER

- TWO COMPLETE PROPORTIONERS IN ONE UNIT
- MULTI-USE - OPEN CELL ON ONE SIDE, CLOSED CELL ON THE OTHER (CAN ALSO BE CONFIGURED FOR POLYUREA)
- SAVE SPACE WITH ONE UNIT, DOUBLE THE CAPABILITY
- ACE CONFORMANCE REPORTING VALIDATES JOB SPECS
- RIG CONNECT ENABLED FOR REAL-TIME SUPPORT

# Delta CPS-HV

## DOUBLE PROPORTIONER



All of the proportioner technology you've come to expect from Akurate Dynamics, but with double the capacity.



- The ACE Conformance Reporting system works seamlessly in the background to monitor all application data. Conformance reporting validates that all application parameters met job specification
- Individual gear pump driven system with integrated software to independently adjust motor speeds based on data points acquired from high resolution flow meters
- Dynamic and intuitive system automatically ensures on-ratio application everytime

## SPECIFICATIONS

APPLICATION	Medium/High Volume Wall Foam, Roofing, Polyurea
TOTAL POWER	17,500 Watts, 230 V, 3 phase
WEIGHT	1200 lbs
DIMENSIONS	40 in (Width) 31.5 in (Depth) 56.5 (Height)
OPERATING TEMP	50 - 130 Degrees Fahrenheit
MAX FLUID WORKING PRESSURE	2200 PSI
MAX FLUID TEMP	150 Degrees Fahrenheit
HEATERS	2 ISO and 2 Resin - 10,000 watts
MOTOR	2 HP x 4 x 750 watts - 3,000 watts
DISPLAY AND COMPUTER	1,500 Watts
DISPLAY DIMENSIONS	19 In (Width) 6 in (Depth) 12 in (Height)
MAX HOSE LENGTH	450'
ALARMS	Descriptive Alarms with Time Stamp